

Accessories for Notching Saw - Typ AS

AS 450

TCT-Saw blade 350 x 3,5 x 40 mm 108 FZ pos.
TCT-Saw blade 450 x 3,5 x 40 mm 110 FZ pos.
Pneumatic control unit, consisting of water separator, pressure reducing valve with manometer and oiler
Pressure reducing valve with manometer and oiler
Roller support, movable, for long profil bars
Digital angle read-out display for two axes

AS-U 450

TCT-Saw blade 400 x 3,8 x 50 mm 96 FZ pos.
TCT-Saw blade 450 x 4,2 x 40 mm 110 FZ pos.
Pneumatic Control Unit, consisting of water separator, pressure reducing valve with manometer and oiler
Pressure reducing valve with manometer
Roller support, movable, for long profil bars
Digital angle read-out display for three axes

AS-V 550

TCT-Saw blade 550 x 4,0 x 50 mm 132 FZ pos.
TCT-Saw blade 350 x 3,5 x 40 mm 108 FZ pos.
Roller support for long profil bars
High speed lubricant 1,0 ltr.

AS-P 550 und AS-P 650

Laser device, line laser for vertical saw blade
Roller support for long profil bars
High speed lubricant 1,0 ltr.

TCT-Saw blade 500 x 4,4 x 50 mm 120 FZ pos.

TCT-Saw blade 550 x 4,0 x 50 mm 132 FZ pos

TCT-Saw blade 650 x 4,4 x 50 mm 140 FZ pos

4-axes CNC control unit for horizontal and vertical saw blade, cutting-height- and cutting-depth adjustment, with digital read-out unit for table-fence angle adjustment

Noise protection package including machine light